

# NORSPRAY® 300

CE

STAINLESS  
STEEL

**Super**  
300



**NORSPRAY® 300** is a complete air operated high pressure paint spray unit atomizing products without air.

**NORSPRAY® 300** can handle a wide range of painting jobs in the maintenance, construction or industrial field. Ideal for spraying heavier viscous paints and coating systems.


**NORSPRAY® 300** has sufficient power and capacity to supply 2 spray guns simultaneously with up to 50 meters of paint spray hose.

## Main advantages:

- Atomizing without air / eliminates overspray.
- Delivery free flow / 13 ltrs min.  
Delivery at 60 cycles / 4 ltrs min.
- Operating 2 spray guns.
- Maximum tip size 1 spray tip 0.29".  
2 spray tips 0.19".
- 16 cycles per liter.
- Air consumption up to:  
35 cfm / 0.98 m<sup>3</sup> min. when operating within pump range.
- Heavy duty cart.
- Stainless steel wetted pump parts.
- Divorced construction of air motor and pump.
- Double ball pump action ensures continuous flow.
- Atomizing heavy viscosity products.
- Large selection of accessories.
- After Sales Service assured by your dealer.

REFERENCE	DESCRIPTION
<b>NOR300</b>	<b>NORSPRAY® 300</b> complete on cart including 30:1 air operated pump with 20 liters suction hose, suction filter, air regulator/filter/oiler with gauge, bleed-type air valve, outlet filter with 60 mesh filter, 7.5 m H.P. paint spray hose, spray gun NW2600 with swivel and NORJET reversible spray tip.
NG5515	NORSPRAY® 30:1 pump only
NG5165	Wall mounting bracket
NW5065	Suction system for 20 liters container
NW5068	Suction system for 200 liters container
NG1050	High pressure filter with 60 M screen
NG1060	Stainless steel high pressure filter with 60 M screen
NW2600	High pressure paint spray gun with NORJET spray tip
NW8025	High pressure spray gun swivel 1/4" MxF
xxx	NORJET spray tips - Consult special spray tip catalog
NG6039	NORFLEX® 3/16" H.P. paint spray hose 7.5 m - 1/4" NPSM-FBE
NG6048	NORFLEX® 1/4" H.P. paint spray hose 7.5 m - 1/4" NPSM-FBE
NG6046	NORFLEX® 1/4" H.P. paint spray hose 15 m - 1/4" NPSM-FBE
NM8010	1/4"x1/4"NPT nipple
NG2030	Repair kit spray gun NW2600
NG2057	Repair kit for air motor NOR300
NG2058	Repair kit displacement pump NOR300

Fluid pressure ratio . . . .	30:1
Delivery free flow . . . .	13 ltrs/min.
Delivery at 60 cycles . . .	4 ltrs/min.
Operating air pressure	
min. . . . .	45 psi/3 bar
max . . . . .	120 psi/8 bar
Maximum fluid pressure	
continued service . . . .	3700 psi/250 bar
Air inlet pump . . . . .	1/2" NPSM-F
Weight . . . . .	29 kg



**NOREXCO®**

**NOREXCO S.A.**

16, rue des Chasseurs - Z.I. Internationale  
74100 Ville-la-Grand - France  
Tél. +33 04 50 38 37 36 - Fax +33 04 50 92 88 44

CE

YOUR DEALER: